

SAFETY DATA SHEET

SEPTONE FIBREGLASS POLISH - SUPERFINE

Infosafe No.: K1H4K
ISSUED Date : 24/01/2014
ISSUED by: ITW AAMTECH

1. IDENTIFICATION

GHS Product Identifier

SEPTONE FIBREGLASS POLISH - SUPERFINE

Product Code

MPFS500, MPFS18

Company Name

ITW AAMTECH (ABN 63 004 235 063)

Address

1-9 NINA LINK DANDENONG SOUTH
VIC 3175 AUSTRALIA

Telephone/Fax Number

Tel: 1800 177 989

Fax: +61 2 9725 4698; 1800 308 556

Emergency phone number

1800 638 556; 1800 039 008; 0800 2436 2255

E-mail Address

info@aamtech.com.au

Recommended use of the chemical and restrictions on use

High gloss paste polish without abrasive

Additional Information

Chemical Name: Not Applicable

Proper shipping name: Not Applicable

Other means of identification: Not Available

CAS number: Not Applicable

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Non-Dangerous Goods.

Non-Hazardous substance.

Signal Word (s)

NOT APPLICABLE

Hazard Statement (s)

Not Applicable

Precautionary statement – Prevention

Not Applicable

Precautionary statement – Response

Not Applicable

Precautionary statement – Storage

Not Applicable

Precautionary statement – Disposal

Not Applicable

Other Information

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

GHS Classification: Not Applicable

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements: Not Applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
White spirit	8052-41-3	10-30 %
Kerosene	8008-20-6	10-30 %
Other ingredients determined to be non-hazardous	Not available	10-30 %
Water	7732-18-5	30-60 %

Other Information

Substances

See section below for composition of Mixtures

4. FIRST-AID MEASURES

Inhalation

If fumes, aerosols or combustion products are inhaled remove from contaminated area.

Other measures are usually unnecessary.

Ingestion

If swallowed do NOT induce vomiting.

If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Observe the patient carefully.

Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Seek medical advice..

Skin

If skin contact occurs:

Immediately remove all contaminated clothing, including footwear.

Flush skin and hair with running water (and soap if available).

Seek medical attention in event of irritation

Eye contact

If this product comes in contact with the eyes:

Wash out immediately with fresh running water.

Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

Seek medical attention without delay; if pain persists or recurs seek medical attention.

Removal of contact lenses after an eye injury should only be undertaken by skilled personnel

Indication of immediate medical attention and special treatment needed if necessary

Treat symptomatically

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

There is no restriction on the type of extinguisher which may be used.

Use extinguishing media suitable for surrounding area

Hazards from Combustion Products

Following the evaporation of water from the product if it is involved in a fire, the residue may burn producing soot, carbon monoxide, carbon dioxide as well as other unidentifiable organic compounds.

Special Protective Equipment for fire fighters

Firefighters are to wear protective equipment appropriate to the principal fire hazard or the source of the fire. No special protective equipment required if this product is involved in a fire.

Specific Methods

Fire Fighting:

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves.

Prevent, by any means available, spillage from entering drains or water courses.

Use water delivered as a fine spray to control fire and cool adjacent area.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected location.

If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard:

Non combustible.

Not considered to be a significant fire risk.

Expansion or decomposition on heating may lead to violent rupture of containers.

Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).

May emit acrid smoke.

Decomposition may produce toxic fumes of:

,
carbon dioxide (CO₂)

,
other pyrolysis products typical of burning organic material

Specific Hazards Arising From The Chemical

None known.

Hazchem Code

Not Applicable

6. ACCIDENTAL RELEASE MEASURES

Clean-up Methods - Small Spillages

Slippery when spilt.

Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes.

Control personal contact with the substance, by using protective equipment.

Contain and absorb spill with sand, earth, inert material or vermiculite.

Wipe up.

Place in a suitable, labelled container for waste disposal

Clean-up Methods - Large Spillages

Slippery when spilt.

Minor hazard.

Clear area of personnel.

Alert Fire Brigade and tell them location and nature of hazard.

Control personal contact with the substance, by using protective equipment as required.

Prevent spillage from entering drains or water ways.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.
Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
Wash area and prevent runoff into drains or waterways.
If contamination of drains or waterways occurs, advise emergency services

Other Information

Personal Protective Equipment advice is contained in Section 8 (EXPOSURE CONTROLS / PERSONAL PROTECTION) of the MSDS.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Limit all unnecessary personal contact.
Wear protective clothing when risk of exposure occurs.
Use in a well-ventilated area.
When handling DO NOT eat, drink or smoke.
Always wash hands with soap and water after handling.
Avoid physical damage to containers.
Use good occupational work practice.
Other information:
Store in original containers.
Keep containers securely sealed.
No smoking, naked lights or ignition sources.
Store in a cool, dry, well-ventilated area.
Store away from incompatible materials and foodstuff containers.
Protect containers against physical damage and check regularly for leaks.
Observe manufacturer's storage and handling recommendations contained within this MSDS.

Conditions for safe storage, including any incompatibilities

Suitable container:
Polyethylene or polypropylene container.
Packing as recommended by manufacturer.
Check all containers are clearly labelled and free from leaks

Storage incompatibility: None known

Other Information

PACKAGE MATERIAL INCOMPATIBILITIES: Not Available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

INGREDIENT DATA

Source: white spirit
Ingredient: White spirits
TWA: 790 (mg/m³)
STEL: Not Available
Peak: Not Available
Notes: (see Chapter 16)

EMERGENCY LIMITS

Ingredient: white spirit
TEEL-0: 500 / 300 / 0.2 / 350 / 100 / 171 / 10(ppm)
TEEL-1: 500 / 300 / 0.6 / 350 / 100 / 513 / 30(ppm)
TEEL-2: 500 / 395 / 200 / 855 / 50(ppm)
TEEL-3: 500 / 395 / 1000 / 1250(ppm)

Ingredient: water
TEEL-0: 500(ppm)
TEEL-1: 500(ppm)
TEEL-2: 500(ppm)
TEEL-3: 500(ppm)

Ingredient: white spirit
Original IDLH: 29,500(mgm3)10,000 / 10,000 [LEL](ppm)
Revised IDLH: 20,000(mgm3)1,100 [LEL] / 1,000 [LEL](ppm)

Appropriate Engineering Controls

General exhaust is adequate under normal operating conditions

Respiratory Protection

Not Applicable

Eye Protection

No special equipment for minor exposure i.e. when handling small quantities.

· OTHERWISE:

· Safety glasses with side shields.

· Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the

wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.

Hand Protection

No special equipment needed when handling small quantities.

OTHERWISE: Wear chemical protective gloves, e.g. PVC.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

'Forsberg Clothing Performance Index'.

The effect(s) of the following substance(s) are taken into account in the computergenerated selection: Septone Spring Air

Material: BUTYL

CPI: A

Material: NEOPRENE

CPI: A

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. - * Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted

Personal Protective Equipment

Not required under normal conditions of use. Wear gloves and chemical goggles if handling large amounts and if splashing is likely to occur. Wear an organic vapour respirator complying with AS/NZS 1715 and AS/NZS1716 if ethanol vapours exceed the exposure limit during use.

Thermal Hazards

Not Available

Body Protection

No special equipment needed when handling small quantities.

OTHERWISE:

Overalls.

Barrier cream.

Eyewash unit.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

Liquid

Appearance

Smooth off-white paste with a slight solvent odour; disperses in water

Odour

Not Available

Solubility in Water

Miscible (g/L)

pH

7.7 (as supplied)

Not Available as a solution(1%)

Vapour Pressure

Not Available (kPa)

Vapour Density (Air=1)

Not Available

Evaporation Rate

>1 water = 1

Physical State

Non Slump Paste

Odour Threshold

Not Available

Viscosity

Not Available (cSt)

Volatile Component

81 w/w (%vol)

Partition Coefficient: n-octanol/water

Not Available

Surface tension

Not Available (dyn/cm or mN/m)

Flash Point

Not Available (°C)

Flammability

Not Available

Auto-Ignition Temperature

Not Available (°C)

Explosion Limit - Upper

Not Available (%)

Explosion Limit - Lower

Not Available (%)

Explosion Properties

Not Available

Molecular Weight

Not Applicable (g/mol)

Oxidising Properties

Not Available

Initial boiling point and boiling range

100-250 (°C)

Relative density

0.900 (Water = 1)

Melting/Freezing Point

Not Available (°C)

Other Information

Taste: Not Available

Gas group: Not Available

VOC g/L: Not Available

10. STABILITY AND REACTIVITY

Reactivity

See section 7 (HANDLING AND STORAGE).

Chemical Stability

Unstable in the presence of incompatible materials.

Product is considered stable.

Hazardous polymerisation will not occur

Conditions to Avoid

See section 7 (HANDLING AND STORAGE).

Incompatible materials

See section 7 (HANDLING AND STORAGE).

Hazardous Decomposition Products

See section 5 (FIREFIGHTING MEASURES).

Possibility of hazardous reactions

See section 7 (HANDLING AND STORAGE).

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

Septone Fibreglass Polish - Superfine

TOXICITY: Not Available

IRRITATION: Not Available

ethanol

TOXICITY: Inhalation (rat) LC50: 20,000 ppm/10h

IRRITATION: Eye (rabbit): 500 mg SEVERE

TOXICITY: Inhalation (rat) LC50: 64000 ppm/4h

IRRITATION: Eye (rabbit):100mg/24hr-moderate

TOXICITY: Oral (rat) LD50: 7060 mg/kg

IRRITATION: Skin (rabbit):20 mg/24hr-moderate

TOXICITY: -

IRRITATION: Skin (rabbit):400 mg (open)-mild

TOXICITY: Not Available

IRRITATION: Not Available

benzyl C8-18 alkyldimethylammonium chloride

TOXICITY: Dermal (rat) LD50: 1420 mg/kg

IRRITATION: -

TOXICITY: Intravenous (mouse) LD50: 16 mg/kg

IRRITATION: -

TOXICITY: Oral (mouse) LD50: 150 mg/kg

IRRITATION: -

TOXICITY: Oral (rat) LD50: 447 mg/kg

IRRITATION: -

TOXICITY: Not Available

IRRITATION: Not Available

water

TOXICITY: Not Available

IRRITATION: Not Available

Not available. Refer to individual constituents.

ETHANOL

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic).

This form of

dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

BENZYL C8-18 ALKYLDIMETHYLAMMONIUM CHLORIDE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

General depressed activity, impaired liver function tests, increased urine volume, changes in bone marrow, chronic pulmonary oedema, gastrointestinal changes recorded. For similar compound benzyl C12-18 alkyldimethyl ammonium chloride CAS RN 68391-01-5:

WATER

No significant acute toxicological data identified in literature search.

CMR STATUS

Not Applicable

Ingestion

Accidental ingestion of the material may be damaging to the health of the individual.

Ingestion may result in nausea, abdominal irritation, pain and vomiting

Inhalation

Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.

Inhalation of vapour is more likely at higher than normal temperatures

Skin

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal

models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Eye

Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or

is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental

animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva

(conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

Chronic Effects

Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following

12. ECOLOGICAL INFORMATION

Ecological information

Toxicity

DO NOT discharge into sewer or waterways.

|Expected to have low toxicity to aquatic organisms. |The hydrocarbons contained in this product are biodegradable, degrading rapidly in air by photo-chemical means

Persistence and degradability

Ingredient: Not Available

Persistence: Water/Soil: Not Available

Persistence: Air: Not Available

Mobility

Ingredient: Not Available

Mobility: Not Available

Bioaccumulative Potential

Ingredient: Not Available

Bioaccumulation: Not Available

Short Summary of Assessment of Environmental Impact

When spilled on land ethanol is apt to volatilize, biodegrade, and leach into the ground water, but no data on the rates of these processes could be found. The fate of ethanol in ground water is unknown. When released into water ethanol will volatilize and probably biodegrade. Ethanol would not be expected to adsorb to sediment or bioconcentrate in fish. When released to the atmosphere ethanol will photodegrade in hours (polluted urban atmosphere) to an estimated range of 4 to 6 days in less polluted areas. Rainout should be significant.

The surfactant contained in this product is readily biodegradable, but is regarded as toxic to aquatic organisms. OECD 302B testing of the quaternary ammonium compound contained in this product indicates that it is readily biodegraded, but it is also regarded as toxic to aquatic organisms.

Therefore, the undiluted product should be prevented from entering waterways. If possible, the expended material should be drained to the sewer as sewerage treatment will greatly reduce damage to water quality. Whilst the aquatic toxicity of the components is relatively high (96 hour maximum safe concentration in the order of 1-5 mg/L), dilution of the product with the large excesses of water present and the relatively rapid biodegradation of the surfactants and quaternary ammonium compound should ensure minimal ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Product Disposal

Recycle wherever possible or consult manufacturer for recycling options.

Consult State Land Waste Management Authority for disposal.

Treat and neutralise with dilute acid at an effluent treatment plant.

Recycle containers, otherwise dispose of in an authorised landfill

14. TRANSPORT INFORMATION

U.N. Number

None Allocated

UN proper shipping name

None Allocated

Transport hazard class(es)

None Allocated

Hazchem Code

Not Applicable

IMDG Marine Pollutant (MP)

NO

Other Information

Land transport (I): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source: 40-7-4-9-0-0-MK-20041022

Ingredient: ethanol

Pollution Category: Not Available

Residual Concentration - Outside Special Area (% w/w): Not Available

Residual Concentration: Not Available

15. REGULATORY INFORMATION

Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

white spirit(8052-41-3.) is found on the following regulatory lists:

'Australia Inventory of Chemical Substances (AICS)', 'Australia Hazardous Substances Information System - Consolidated Lists', 'OECD

Existing Chemicals Database', 'OECD List of High Production Volume (HPV) Chemicals', 'Australia High Volume Industrial Chemical List (HVICL)', 'International Numbering System for Food Additives', 'International Council of Chemical Associations (ICCA) - High Production Volume List', 'FisherTransport Information', 'Sigma-AldrichTransport Information', 'GESAMP/EHS Composite List - GESAMP Hazard Profiles', 'IMO IBC Code Chapter 17: Summary of minimum requirements', 'CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP', 'Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5', 'Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6', 'Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)', 'Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)', 'Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C'

water(7732-18-5*) is found on the following regulatory lists:

'Australia Inventory of Chemical Substances (AICS)', 'OSPAR National List of Candidates for Substitution – Norway', 'OECD List of High Production Volume (HPV) Chemicals', 'Australia High Volume Industrial Chemical List (HVICL)', 'WHO Model List of Essential Medicines - Adults', 'International Fragrance Association (IFRA) Survey: Transparency List', 'Sigma-AldrichTransport Information', 'IMO IBC Code Chapter 18: List of products to which the Code does not apply'

16. OTHER INFORMATION

Contact Person/Point

Australia:

24 HOUR EMERGENCY CONTACT (ACOHs Pty Ltd): 1 800 638 556

Poisons Information Centre (Australia): 13 11 26

New Zealand:

24 HOUR EMERGENCY CONTACT (ACOHs Pty Ltd): 0800 154 666

NZ National Poisons Centre (24 Hour): 0800 764 766

Empirical Formula & Structural Formula

Not Applicable

Other Information

Version No: 4.1.1.1

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This SDS has been transcribed into Infosafe GHS format from an original, issued by the manufacturer on the date shown.

Any disclaimer by the manufacturer may not be included in the transcription.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.