



SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK PVC CEMENT N CLEAR

Product Code(s)
30840493
30840467; 30840491; 30840493

Other means of identification

Proper Shipping Name Adhesives

UN number or ID number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against Consumer use

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

| | |
|---|---------------------|
| Flammable liquids | Category 2 - (H225) |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 - (H332) |
| Skin corrosion/irritation | Category 2 - (H315) |
| Serious eye damage/eye irritation | Category 1 - (H318) |
| Specific target organ toxicity (single exposure) | Category 3 - (H336) |

Label elements

Flame
Exclamation mark

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Corrosion



Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H318 - Causes serious eye damage
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P264 - Wash face, hands and any exposed skin thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P235 - Keep cool
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 - Wash contaminated clothing before reuse
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P370 + P378 - In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

May be harmful if swallowed
May be harmful in contact with skin
In use, may form flammable/explosive vapor-air mixture

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

| Chemical name | CAS No. | Weight-% |
|---------------------------|-------------|----------|
| Methyl ethyl ketone | 78-93-3 | 30 - 60 |
| Cyclohexanone | 108-94-1 | 10 - <30 |
| Acetone | 67-64-1 | 10 - <30 |
| Non-hazardous ingredients | Proprietary | Balance |

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical advice/attention. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Get medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides. Carbon dioxide (CO₂). Hydrogen chloride. Hydrochloric Acid.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3YE

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Keep from any possible contact with water. Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

using this product. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Keep away from water or moist air.

Recommended storage temperature

Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

| Chemical name | Australia |
|--------------------------------|---|
| Methyl ethyl ketone 78-93-3 | 150 ppm TWA 445 mg/m ³ TWA 300 ppm STEL 890 mg/m ³ STEL |
| Cyclohexanone 108-94-1 | 25 ppm TWA 100 mg/m ³ TWA |
| Acetone 67-64-1 | 500 ppm TWA 1185 mg/m ³ TWA 1000 ppm STEL 2375 mg/m ³ STEL |

Appropriate engineering controls

Engineering controls

Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection

Wear suitable gloves. Impervious gloves. Butyl rubber. Nitrile rubber. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Recommended filter type: Organic gases and vapors

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

filter conforming to EN 14387.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

| | |
|----------------|--------------------------|
| Physical state | Liquid |
| Appearance | Liquid |
| Color | Clear, colorless |
| Odor | Ketone |
| Odor threshold | No information available |

| Property | Values | Remarks • Method |
|---|--------------------------------------|-----------------------------------|
| pH | No data available | Not applicable Insoluble in water |
| pH (as aqueous solution) | No data available | |
| Melting point / freezing point | No data available | |
| Initial boiling point and boiling range | 56 °C | |
| Flash point | -4 °C | (Methyl Ethyl Ketone) |
| Evaporation rate | No data available | |
| Flammability | Not applicable for liquids | |
| Flammability Limit in Air | | |
| Upper flammability or explosive limits | 11.5 | |
| Lower flammability or explosive limits | 1.8 | |
| Vapor pressure | 9500 | |
| Relative vapor density | > 1 | |
| Relative density | 0.94 | |
| Water solubility | partially soluble | |
| Solubility(ies) | No data available | |
| Partition coefficient | No data available | |
| Autoignition temperature | 515 °C | |
| Decomposition temperature | No data available | |
| Kinematic viscosity | No data available mm ² /s | |
| Dynamic viscosity | approx 600 - 900 mPa s | |
| Explosive properties | No information available | |
| Oxidizing properties | No information available | |

Other information

| | |
|-------------------|--------------------------|
| Solid content (%) | approx 21.5 |
| Density | No information available |
| VOC Content (%) | 732 g/L |

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Unstable on exposure to moisture.

Explosion data

| | |
|----------------------------------|-------|
| Sensitivity to mechanical impact | None. |
| Sensitivity to static discharge | Yes. |

Possibility of hazardous reactions

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat. Keep from any possible contact with water.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Coughing and/ or wheezing.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 2,926.50
ATEmix (dermal) 3,633.00
ATEmix (inhalation-vapor) 36.30
ATEmix (inhalation-dust/mist) 4.95

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------|----------------------|--------------------------------------|-------------------------|
| Methyl ethyl ketone | =2483 mg/kg (Rattus) | = 5000 mg/kg (Oryctolagus cuniculus) | =11700 ppm (Rattus) 4 h |
| Cyclohexanone | =1535 mg/kg (Rattus) | = 947 mg/kg (Oryctolagus cuniculus) | =8000 ppm (Rattus) 4 h |
| Acetone | =5800 mg/kg (Rattus) | >15800 mg/Kg (Rattus) | =79 mg/l(Rattus) 4 h |

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

| Component Information | | | | | |
|---|---------|----------------|----------------|---------------|----------|
| Methyl ethyl ketone (78-93-3) | | | | | |
| Method | Species | Exposure route | Effective dose | Exposure time | Results |
| OECD Test No. 405: Acute Eye Irritation/Corrosion | Rabbit | eye | | | irritant |

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

| Component Information | | | |
|---------------------------------------|------------|----------------|--|
| Methyl ethyl ketone (78-93-3) | | | |
| Method | Species | Exposure route | Results |
| OECD Test No. 406: Skin Sensitization | Guinea pig | Dermal | No sensitization responses were observed |

Acetone (67-64-1)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical name | SafeWork Australia | European Union | IARC |
|---------------------------|--------------------|----------------|---------|
| Cyclohexanone 108-94-1 | | | Group 3 |

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness. May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

| Chemical name | Algae/aquatic plants | Fish | Toxicity to microorganisms | Crustacea |
|--------------------------------|---|---|---|--|
| Methyl ethyl ketone 78-93-3 | EC50=1972 mg/l (Pseudokirchneriella subcapitata) | LC50: 3130 - 3320mg/L (96h, Pimephales promelas) | EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min | EC50 48 h > 308 mg/L (Daphnia magna) |

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

| | | | | |
|---------------------------|--|---|--|---|
| Cyclohexanone 108-94-1 | EC50: =20mg/L (96h, Chlorella vulgaris) | LC50 96 h 481 - 578 mg/L (Pimephales promelas flow-through) | EC50 = 18.5 mg/L 5 min EC50 = 21.3 mg/L 10 min EC50 = 25 mg/L 5 min | EC50: =800mg/L (24h, Daphnia magna) |
| Acetone 67-64-1 | - | LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss) | EC50 = 14500 mg/L 15 min | EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static) |

Persistence and degradability

Persistence and degradability No information available.

| Component Information | | | |
|---|---------------|----------------|----------------------------|
| Methyl ethyl ketone (78-93-3) | | | |
| Method | Exposure time | Value | Results |
| OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D) | 28 days | biodegradation | 98 % Readily biodegradable |
| Acetone (67-64-1) | | | |
| Method | Exposure time | Value | Results |
| OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B) | 28 days | biodegradation | 91 % Readily biodegradable |

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

| Chemical name | Partition coefficient |
|--------------------------------|-----------------------|
| Methyl ethyl ketone 78-93-3 | 0.3 |
| Cyclohexanone 108-94-1 | 0.86 |
| Acetone 67-64-1 | -0.24 |

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

ADG

UN number or ID number UN1133
UN proper shipping name Adhesives
Transport hazard class(es) 3
Packing group II
Special Provisions *
ADG Limited Quantity 5 L
Description UN1133, Adhesives, 3, II

Hazchem code •3YE

IATA

UN number or ID number UN1133
Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A3
Limited Quantity (LQ) 1 L
Description UN1133, Adhesives, 3, II

IMDG

UN number or ID number UN1133
Transport hazard class(es) 3
Packing group II
EmS-No F-E, S-D
Limited Quantity (LQ) 5 L
Marine pollutant NP
Description UN1133, Adhesives, 3, II, (-4°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000
200

National pollutant inventory

Subject to reporting requirement

| Chemical name | National pollutant inventory |
|--------------------------------|---|
| Methyl ethyl ketone 78-93-3 | 10 tonne/yr Threshold category 1 20 MWh Threshold category 2b total 60000 MWh Threshold category 2b total |

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

| | |
|---------------------------|---|
| | 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total |
| Cyclohexanone 108-94-1 | 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total |
| Acetone 67-64-1 | 10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total |

International Inventories

| | |
|--------------|--------|
| AICS | Listed |
| NZIoC | Listed |
| ENCS | Listed |
| IECSC | Listed |
| KECL | Listed |
| PICCS | Listed |

Legend:

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

SAFETY DATA SHEET

BOSTIK PVC CEMENT N CLEAR
Revision Number 1

Revision date 11-Aug-2021
Supersedes Date: 11-Aug-2021

Revision date 11-Aug-2021

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| | | | |
|---------|-----------------------------|------|----------------------------------|
| TWA | TWA (time-weighted average) | STEL | STEL (Short Term Exposure Limit) |
| Ceiling | Maximum limit value | * | Skin designation |
| C | Carcinogen | | |

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet