SAFETY DATA SHEET

SELLEYS KWIK GRIP HORIZONTAL

Infosafe No.: MTS80 ISSUED Date : 18/10/2021 ISSUED by: SELLEYS, A DIVISION OF DULUXGROUP (AUSTRALIA) PTY LTD

Section 1 - Identification

Product Identifier SELLEYS KWIK GRIP HORIZONTAL

Company Name

SELLEYS, A DIVISION OF DULUXGROUP (AUSTRALIA) PTY LTD (ABN 67 000 049 427)

Address

1956 Dandenong Road Clayton VIC 3168 AUSTRALIA

Telephone/Fax Number Tel: 1300 555 205

Emergency Phone Number Australia – 1800 220 770; New Zealand – 0800 220 770

Recommended use of the chemical and restrictions on use

Bonding laminated plastics, rubber, leather, canvas, wood, cork, hardboard, metals and fibrous cement sheeting.

Other Names

Name	Product Code
SELLEYS KWIK GRIP HORIZONTAL	Reference No: SELGHSEN000172
KWIK GRIP HORIZONTAL 50ML	100039
KWIK GRIP HORIZONTAL 100ML	100044
KWIK GRIP HORIZONTAL 250ML	100045
KWIK GRIP HORIZONTAL 500ML	100043
KWIK GRIP HORIZONTAL 1L	100042
KWIK GRIP HORIZONTAL 2L	100041
KWIK GRIP HORIZONTAL 4L	100089
KWIK GRIP HORIZONTAL 150KG EXP	100334

Other Information

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Orice Limited and its subsidiaries cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture Eye Damage/Irritation: Category 2A Flammable Liquids: Category 2 Page 1/10

Skin Corrosion/Irritation: Category 2 STOT Single Exposure: Category 3 (narcotic)

Signal Word (s) DANGER

Hazard Statement (s)

H225 Highly flammable liquid and vapour.H315 Causes skin irritation.H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

Pictogram (s)

Flame, Exclamation mark



Precautionary Statement – Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/and all other/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement – Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

Precautionary Statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statement – Disposal

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Precautionary Statement – General

P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use.

Other Information

This material is hazardous according tothecriteria of Safe Work Australia GHS 7.

Poison Schedule: Not Applicable

DANGEROUS GOOD CLASSIFICATION:

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land". Dangerous Goods Class: 3

Section 3 - Composition and Information on Ingredients

ngredients		
Name	CAS	Proportion
n-Propyl acetate	109-60-4	30-60 %(w/w)
Naphtha, petroleum, hydrotreated light	64742-49-0	30-60 %(w/w)
Ingredients determined to be non-hazardous or below reporting limits		Balance
Methyl Ethyl Ketone	78-93-3	1-10 %(w/w)

Other Information

Synonyms / Bar Code Kwik Grip 50mL 9300697101174 Kwik Grip 100mL 9300697104595 Kwik Grip 250mL 9300697118936 Kwik Grip 500mL 9300697102287 Kwik Grip 1L 9300697102270 Kwik Grip 2L 9300697102263 Kwik Grip 4L 9300697102256

Section 4 - First Aid Measures

First Aid Measures

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation

Remove victim from exposure -avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Ingestion

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

Skin

If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Advice to Doctor

Treat symptomatically.

Protection for First Aiders

Wear safety shoes, overalls, gloves, safety glasses, respirator.Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.Available information suggests that gloves made from nitrile rubbershould be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific Methods

Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray.On burning ordecomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

Specific hazards arising from the chemical

Highly flammable liquid and vapour.May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Hazchem Code

•3YE

Section 6 - Accidental Release Measures

Clean-up Methods - Small Spillages

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

Clean-up Methods - Large Spillages

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Other Information

Dangerous Goods - Initial Emergency Response Guide No: 14

Section 7 - Handling and Storage

Precautions for Safe Handling

Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition.Store locked up.Keep container standing upright.Keep containers closed when not in use -check regularly for leaks.

Other Information

This material is classified as aClass 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail"and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land"and must be stored in accordance with the relevant regulations.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

National occupational exposure limits: Methyl ethyl ketone (MEK) TWA ppm / TWA mg/m³ / STEL ppm / STEL mg/m³ / NOTICES 150 445 300 890 -

n-Propyl acetate

TWA ppm / TWA mg/m³ / STEL ppm / STEL mg/m³ / NOTICES 200 835 250 1040 -

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed durin product manufacture.

Biological Monitoring

As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Controls

Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air -prevent concentration in hollows or sumps. DoNOT enter confined spaces where vapour may have collected.

Personal Protective Equipment

SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES, RESPIRATOR.

Wear safety shoes, overalls, gloves, safety glasses, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.Available information suggests that gloves made from nitrile rubbershould be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene Measures

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Properties	Description	Properties	Description
Form	Liquid	Colour	Yellow
Odour	Solvent	Melting Point	Not available
Boiling Point	Not available	Solubility	Insoluble in water. Soluble in organic solvents.
Specific Gravity	0.89	рН	Not applicable
Vapour Pressure	Not available (20 °C)	Relative Vapour Density (Air=1)	>1
Viscosity	>1,000 mm²/s @ 40 °C	Flash Point	<23°C (solvent)
Auto-Ignition Temperature	Not available	Flammable Limits - Lower	Not available
Flammable Limits - Upper	Not available		

Section 9 - Physical and Chemical Properties

Other Information

Total VOC (g/Litre): Not available

(Typical values only - consult specification sheet)

Section 10 - Stability and Reactivity

Chemical Stability

This material is thermally stable when stored and used as directed.

Possibility of hazardous reactions

No known hazardous reactions.

Conditions to Avoid

Elevated temperatures and sources of ignition.

Incompatible Materials

Oxidising agents.

Hazardous Decomposition Products

Oxides of carbon and nitrogen, smoke and other toxic fumes.

Section 11 - Toxicological Information

Acute Toxicity - Oral

This material has been classified as not hazardousfor acute ingestion exposure. Acute toxicity estimate (based on ingredients): LD50>2,000 mg/Kg bw

Acute Toxicity - Dermal

This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD50>2,000 mg/Kg bw

Acute Toxicity - Inhalation

This material has been classified as not hazardousfor acuteinhalationexposure. Acute toxicity estimate (based on ingredients):LC50> 20.0mg/Lfor vapours orLC50> 5.0 mg/L for dust and mist.

Ingestion

Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Inhalation

Material may be an irritant to mucous membranes and respiratory tract.Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Skin

Contact with skin will result in irritation.

Skin Corrosion/Irritation

Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Eye

An eye irritant.

Serious Eye Damage/Irritation

Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes).

Respiratory Sensitisation

Inhalation: this material has been classified as not a respiratory sensitiser.

Skin Sensitisation

Skin: this material has been classified as not a skin sensitiser.

Carcinogenicity

This material has been classified as not a carcinogen.

Reproductive Toxicity

(including via lactation): This material has been classified as not a reproductive toxicant.

STOT - Single Exposure

This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in depression of the central nervous system.

STOT - Repeated Exposure

This material has been classified asnot a specific hazard to target organs by repeat exposure.

Aspiration Hazard

This material has been classified as not an aspiration hazard.

Mutagenicity

This material has been classified as not a mutagen.

Delayed health effects from exposure

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are: For WSA format, please refer to Health Effects Section for acute effects.

Section 12 - Ecological Information

Ecological Information

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): >100 mg/L

Long-term aquatic hazard: This material has been classified as a Category Chronic 2 Hazard (9.1B New Zealand). Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): 1 -10 mg/L, where the substance is not rapidly degradable and/or BCF = 500 and/or log Kow = 4.

Ecotoxicity

No information available.

Persistence and degradability No information available.

Mobility No information available.

Bioaccumulative Potential No information available.

Section 13 - Disposal Considerations

Waste Disposal

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

Section 14 - Transport Information

UN Number 1133 Proper Shipping Name ADHESIVES Transport Hazard Class 3 Packing Group II Hazchem Code • 3YE IERG Number 14

Page 7 / 10

IATA UN Number

1133

IATA Proper Shipping Name ADHESIVES

IATA Transport Hazard Class

3

IATA Packing Group Ш

IMDG UN Number 1133

IMDG Proper Shipping Name ADHESIVES

IMDG Transport Hazard Class

3

IMDG Packing Group

Ш

Additional Information

ROAD AND RAIL TRANSPORT:

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 1133 **Dangerous Goods Class: 3** Packing Group: II Hazchem Code: ·3YE **Emergency Response Guide No: 14** Limited Quantities: 5 L **Proper Shipping Name: ADHESIVES** Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic

gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT:

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code. UN No: 1133 **Dangerous Goods Class: 3** Packing Group: II **Proper Shipping Name: ADHESIVES**

AIR TRANSPORT:

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air. UN No: 1133 **Dangerous Goods Class: 3** Packing Group: II **Proper Shipping Name: ADHESIVES**

Section 15 - Regulatory Information

Regulatory Information

This material is not subject to the following international agreements: Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent)

This material is subject to the following international agreements:

Basel Convention (Hazardous Waste):

Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish

International Convention for the Prevention of Pollution from Ships (MARPOL): Annex III - Harmful Substances carried in Packaged Form

This material/constituent(s) is covered by the following requirements: The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Not Applicable.

NZ EPA Status: All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

HSNO Group Standard: HSR002662 -Surface Coatings and Colourants (Flammable) Group Standard 2020

Poisons Schedule

N/A

Global Inventory Status

Country/Region Inventory	Status Description	Country/Region Inventory	Status Description
	AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).		

Section 16 - Any Other Relevant Information

Revisions Made

Reason for issue: Revised

Contact Person/Point

This Material Safety Data Sheet has been prepared by SHE Pacific Pty Ltd on behalf of Orica Ltd and its subsidiary companies.

Contact Point: SHE Pacific Pty Ltd, MSDS Services

Within Australia: Telephone: 1 800 624 132 Facsimile: (03) 9665 7929

Outside Australia: Telephone: +61 3 9665 7500 Facsimile: +61 3 9665 7929

For further copies of this sheet or other product information contact Selleys Pty Limited Customer Service.

Phone: 1300 555 205 (Australia wide) Fax: 1300 555 305 (Australia wide).

User Codes

User Title Label	User Codes
Wis Numbers	03260614
Wis Numbers	04110802
Wis Numbers	04110909
Wis Numbers	04111005
Wis Numbers	04111102
Wis Numbers	04111209
Wis Numbers	04111306
Wis Numbers	04111403

Other Information

Reference No: SELGHSEN000172

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS has been transcribed into Infosafe GHS format from an original, issued by the manufacturer on the date shown. Any disclaimer by the manufacturer may not be included in the transcription.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.