



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	39-2537-7	Version number:	4.00
Issue Date:	28/11/2022	Supersedes date:	14/09/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Metal Bonder Acrylic Adhesive DP8407NS, Gray, Part B

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Professional

For Industrial or Professional use only.

1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for

Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure: sensory organs.

Precautionary statements

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280F	Wear respiratory protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

P370 + P378

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:P403 + P235
P405

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

P501

Dispose of contents/container in accordance with applicable
local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Causes mild skin irritation.

May be harmful if inhaled.

Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Methyl Methacrylate	80-62-6	45 - 65
Acrylonitrile-Butadiene Polymers	Trade Secret	10 - 30
2-hydroxyethyl methacrylate	868-77-9	1 - 10
Fillers	Trade Secret	1 - 10
Barium diboron tetraoxide	13701-59-2	0.1 - 5
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	0.1 - 5
Hydroxypropyl Methacrylate	27813-02-1	0.1 - 5
Urethane acrylate oligomer	Trade Secret	0.1 - 5
Polyolmethacrylate Phosphate Esters	95175-93-2	< 3
Copper Naphthenates	1338-02-9	< 0.2

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin

reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.

Carbon dioxide.

Hydrogen Chloride

Hydrogen cyanide.

Oxides of nitrogen.

Condition

During combustion.

During combustion.

During combustion.

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: •3YE

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m ³ ;TWA(as Cu dust or mist):1 mg/m ³	
Barium, soluble compounds	13701-59-2	ACGIH	TWA(as Ba):0.5 mg/m ³	A4: Not class. as human carcin
Barium, soluble compounds	13701-59-2	Australia OELs	TWA(as Ba)(8 hours):0.5 mg/m ³	
Paraffin oil	64742-55-8	Australia OELs	TWA(as mist)(8 hours):5 mg/m ³	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	A4: Not class. as human carcin, Dermal Sensitizer
Methyl Methacrylate	80-62-6	Australia OELs	TWA(8 hours):208 mg/m ³ (50 ppm);STEL(15 minutes):416 mg/m ³ (100 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitizer

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Brown
Odour	Methacrylate
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	$\geq 37.8^{\circ}\text{C}$
Flash point	$\geq 10^{\circ}\text{C}$ [Test Method: Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>

Density	1.01 g/ml
Relative density	1.01 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	12,000 - 18,000 mPa-s
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H ₂ O & exempt solvents	20.2 g/l [Details:when used as intended with Part A]
VOC less H ₂ O & exempt solvents	2 % [Details:when used as intended with Part A]
Molecular weight	Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Heat.

Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Acrylonitrile-Butadiene Polymers	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile-Butadiene Polymers	Ingestion	Rat	LD50 > 30,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Polyolmethacrylate Phosphate Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Polyolmethacrylate Phosphate Esters	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Fillers	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fillers	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fillers	Ingestion	Rat	LD50 > 5,110 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Barium diboron tetraoxide	Dermal	Rabbit	LD50 > 2,000 mg/kg
Barium diboron tetraoxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3.54 mg/l
Barium diboron tetraoxide	Ingestion	Rat	LD50 530 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Methacrylate	Human and animal	Mild irritant
Acrylonitrile-Butadiene Polymers	Professional judgement	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
Polyolmethacrylate Phosphate Esters	Not available	Irritant
Fillers	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Barium diboron tetraoxide	Rabbit	No significant irritation
Copper Naphthenates	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymers	Professional judgement	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
Polyolmethacrylate Phosphate Esters	Not available	Corrosive
Fillers	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Barium diboron tetraoxide	Rabbit	No significant irritation
Copper Naphthenates	In vitro data	No significant irritation

Skin Sensitisation

Name	Species	Value
Methyl Methacrylate	Human and animal	Sensitising
2-hydroxyethyl methacrylate	Human and animal	Sensitising
Fillers	Human and animal	Not classified
Hydroxypropyl Methacrylate	Human and animal	Sensitising
Barium diboron tetraoxide	Guinea pig	Not classified
Copper Naphthenates	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
Methyl Methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Fillers	In Vitro	Not mutagenic
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Barium diboron tetraoxide	In Vitro	Not mutagenic
Barium diboron tetraoxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
Fillers	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Inhalation	Not classified for male reproduction	Mouse	NOAEL 36.9 mg/l	
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Fillers	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fillers	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fillers	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Barium diboron tetraoxide	Ingestion	Toxic to female reproduction	Rat	NOAEL 800 mg/kg/day	90 days
Barium diboron tetraoxide	Ingestion	Toxic to development	Rabbit	NOAEL 20 mg/kg/day	during organogenesis
Barium diboron tetraoxide	Ingestion	Toxic to male reproduction	Rat	NOAEL 350 mg/kg/day	90 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Polyolmethacrylate Phosphate Esters	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for	similar health hazards	NOAEL Not available	

			classification			
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Barium diboron tetraoxide	Ingestion	nervous system	Not classified	Rat	NOAEL 200 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Fillers	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Barium diboron tetraoxide	Ingestion	hematopoietic system liver heart skin endocrine system bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 700 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 **Control Parameters** of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Methyl Methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
Methyl Methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
Methyl Methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
Methyl Methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
Methyl Methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
Methyl Methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
Acrylonitrile-Butadiene Polymers	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Fillers	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Barium diboron tetraoxide	13701-59-2	Activated sludge	Experimental	3 hours	NOEC	100 mg/l
Barium diboron tetraoxide	13701-59-2	Green algae	Experimental	72 hours	EC50	7.8 mg/l

Barium diboron tetraoxide	13701-59-2	Rainbow trout	Experimental	96 hours	LC50	62 mg/l
Barium diboron tetraoxide	13701-59-2	Water flea	Experimental	48 hours	EC50	20.3 mg/l
Barium diboron tetraoxide	13701-59-2	Green algae	Experimental	72 hours	NOEC	1.1 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Fathead minnow	Estimated	96 hours	LL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	48 hours	EL50	>100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Green algae	Estimated	72 hours	NOEL	100 mg/l
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Bacteria	Experimental	N/A	EC10	1,140 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Green algae	Experimental	72 hours	EC50	>97.2 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
Urethane acrylate oligomer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Polyolmethacrylate Phosphate Esters	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Copper Naphthenates	1338-02-9	Green algae	Estimated	72 hours	EC50	0.629 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
Copper Naphthenates	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.0702 mg/l
Copper Naphthenates	1338-02-9	Algae or other aquatic plants	Estimated	N/A	NOEC	0.132 mg/l
Copper Naphthenates	1338-02-9	Fathead minnow	Estimated	32 days	EC10	0.0354 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	21 days	NOEC	0.0756 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl Methacrylate	80-62-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThOD	OECD 301C - MITI test (I)
Acrylonitrile-Butadiene Polymers	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/COD	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
Fillers	Trade Secret	Data not available-	N/A	N/A	N/A	N/A

		insufficient				
Barium diboron tetraoxide	13701-59-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Estimated Biodegradation	28 days	CO2 evolution	22 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Hydroxypropyl Methacrylate	27813-02-1	Experimental Biodegradation	28 days	BOD	81 %BOD/ThOD	OECD 301C - MITI test (I)
Urethane acrylate oligomer	Trade Secret	Data not available-insufficient	N/A	N/A	N/A	N/A
Polyolmethacrylate Phosphate Esters	95175-93-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Copper Naphthenates	1338-02-9	Data not available-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Methyl Methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flask mtd
Acrylonitrile-Butadiene Polymers	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flask mtd
Fillers	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Barium diboron tetraoxide	13701-59-2	Experimental Bioconcentration		Log Kow	-0.70	
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydroxypropyl Methacrylate	27813-02-1	Experimental Bioconcentration		Log Kow	0.97	
Urethane acrylate oligomer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyolmethacrylate Phosphate Esters	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Copper Naphthenates	1338-02-9	Estimated BCF - Fish	42 days	Bioaccumulation factor	≤27	OECD305-Bioconcentration

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: •3YE

IERG: 14

International Air Transport Association (IATA) - Air Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1133

Proper shipping name: ADHESIVES

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

An ingredient(s) in this product is being introduced under the no unreasonable risk non-cosmetic (<100 Kg) exemption provisions specified in Section 21(4) of the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

Poison Schedule: This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au