

## Section 1 - Identification of The Material and Supplier

Hogans Wholesale  
66 Elizabeth St  
Wetherill Park, NSW 2164

Phone: 02 9756 5913 (office hours)  
Fax: 02 9756 6473

**Chemical nature:** Zinc powder in a suitable solvent, presented as an aerosol.  
**Trade Name:** **Cold Gal 400g**  
**Product Use:** Zinc rich primer for steel.  
**Creation Date:** **December, 2016**  
**This version issued:** **December, 2021** and is valid for 5 years from this date.  
**Poisons Information Centre: Phone 13 1126 from anywhere in Australia**

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

**SUSMP Classification:** None allocated.

**ADG Classification:** 2

**UN Number:** 1950, AEROSOLS



### GHS Signal word: DANGER

Flammable aerosols Category 2

Substances and mixtures which, in contact with water, emit flammable gases Category 1

Acute Toxicity Dermal Category 4

Skin Irritation Category 2

Eye irritation Category 2B

Acute Toxicity Inhalation Category 4

Specific Target Organ Toxicity Inhal - Single Exposure Category 3

Specific Target Organ Toxicity Oral - Single Exposure Category 3

Specific Target Organ toxicity Dermal - repeated exposure Category 2

Hazardous to aquatic environment Short term/Chronic Category 1

### HAZARD STATEMENT:

H223: Flammable aerosol

H229: Pressurised container: may burst if heated.

H260: In contact with water releases flammable gases which may ignite spontaneously.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H320: Causes eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

H410: Very toxic to aquatic life with long lasting effects.

### PREVENTION

P102: Keep out of reach of children.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P271: Use only outdoors or in a well ventilated area.

P273: Avoid release to the environment.

## SAFETY DATA SHEET

P280: Wear protective gloves, protective clothing and eye or face protection.

#### RESPONSE

P314: Get medical advice or attention if you feel unwell.

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P372: Explosion risk in case of fire.

P391: Collect spillage.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

#### STORAGE

P405: Store locked up.

P403: Store in a well-ventilated place.

P410+P412: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C.

#### DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

### Emergency Overview

**Physical Description & Colour:** Grey liquid dispensed as an aerosol spray.

**Odour:** Hydrocarbon solvent odour.

**Major Health Hazards:** may cause serious damage to health by prolonged exposure, irritating to eyes and skin, harmful if inhaled, vapours may cause drowsiness and dizziness.

### Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Zinc (powder)	7440-66-6	>60	not set	not set
Xylene	1330-20-7	10-30	350	655
Dimethyl ether	115-10-6	10-30	760	950
Solvent naphtha (petroleum), light arom.	64742-95-6	<10	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

#### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

**Inhalation:** If symptoms of poisoning become evident, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

**Skin Contact:** Quickly and gently blot away excess liquid. Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

**Eye Contact:** Quickly and gently blot material from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to

### SAFETY DATA SHEET

rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

**Flash point:** -41°C, Dimethyl ether

**Upper Flammability Limit:** 26.7%

**Lower Flammability Limit:** 3.45%

**Autoignition temperature:** 350°C

**Flammability Class:** Flammable Category 2 (GHS); Highly Flammable (AS1940).

## Section 6 - Accidental Release Measures

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep large quantities of Dangerous Goods, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Xylene	350	655
Dimethyl ether	760	950

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** Prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

## SAFETY DATA SHEET

**Protective Material Types:** We suggest that protective clothing be made from the following materials: polyvinyl alcohol, Teflon, PE/EVAL.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations and safety deluge showers should, if practical, be provided near to where this product is being handled commercially.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Grey liquid dispensed as an aerosol spray.
<b>Odour:</b>	Hydrocarbon solvent odour.
<b>Boiling Point:</b>	Not available.
<b>Freezing/Melting Point:</b>	Liquid/aerosol at normal room temperatures.
<b>Volatiles:</b>	Non zinc component.
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	1.8-1.9
<b>Water Solubility:</b>	Insoluble.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water Distribution:</b>	No data.
<b>Autoignition temp:</b>	350°C

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** acids, bases, oxidising agents. In contact with water, zinc, especially if finely divided, may release flammable hydrogen gas.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Zinc compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## Section 11 - Toxicological Information

### Local Effects:

**Target Organs:** There is no data to hand indicating any particular target organs.

Solvent Naphtha (petroleum), Light Arom. is a SWA Class 2 Mutagen, likely to be mutagenic to humans.

## Classification of Hazardous Ingredients

### Ingredient

#### Zinc powder (stabilised)

- Hazardous to the aquatic environment (acute) - category 1
- Hazardous to the aquatic environment (chronic) - category 1

#### Xylene

- Flammable liquid – category 3
- Acute toxicity – category 4
- Acute toxicity – category 4
- Specific target organ toxicity (single exposure) – category 3
- Skin irritation – category 2
- Aspiration hazard – category 1

#### Dimethyl Ether

## SAFETY DATA SHEET

- Flammable gas - category 1
- Gas under pressure

Solvent Naphtha (petroleum), Light Arom.

- Aspiration hazard – category 1
- Carcinogenicity – category 1A
- Germ cell mutagenicity – category 1B
- Eye irritation – category 2A
- Skin irritation – category 2
- Specific target organ toxicity (repeated exposure) – category 1

**NOTE:** Some of the above classifications relate to impurities found in these ingredients. These do not apply where impurities are not present at hazardous concentrations.

## Potential Health Effects

### Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

### Skin Contact:

**Short Term Exposure:** Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short Term Exposure:** If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Xylene is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

## Section 12 - Ecological Information

Insufficient data to be sure of status.

## Section 13 - Disposal Considerations

**Disposal:** Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service. Do not puncture or incinerate aerosol cans, even when empty.

## Section 14 - Transport Information

**Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.**

**UN Number:** 1950, AEROSOLS

**Hazchem Code:** 2YE

**Special Provisions:** 63, 190, 277, 327, 344, 381

**Limited quantities:** ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

**Dangerous Goods Class:** Class 2.1: Flammable gases.

**Packing Group:** Not set

**Packing Instruction:** P207, LP200

## SAFETY DATA SHEET

Issued by: Hogans Wholesale

Phone: 02 9756 5913 (office hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

### Section 15 - Regulatory Information

**AICS:** All of the significant ingredients in this formulation are compliant with NICNAS regulations. The following ingredients: Xylene, Solvent naphtha (petroleum), light arom., are mentioned in the SUSMP.

### Section 16 - Other Information

**This SDS contains only safety-related information. For other data see product literature.**

#### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 <sup>th</sup> edition)
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Code</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>SUSMP</b>	Standard for the Uniform Scheduling of Medicines & Poisons
<b>UN Number</b>	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

Copyright © Kilford & Kilford Pty Ltd, December, 2021.

<http://www.kilford.com.au/> Phone (02)8321 8866

### SAFETY DATA SHEET